



US007546498B1

(12) **United States Patent**
Tang et al.

(10) **Patent No.:** **US 7,546,498 B1**
(45) **Date of Patent:** **Jun. 9, 2009**

(54) **PROGRAMMABLE LOGIC DEVICES WITH CUSTOM IDENTIFICATION SYSTEMS AND METHODS**

7,301,836 B1 * 11/2007 Raghavan et al. 365/201
2003/0163773 A1 * 8/2003 O'Brien et al. 714/726
2006/0179373 A1 * 8/2006 Ishikawa 714/727

(75) Inventors: **Howard Tang**, San Jose, CA (US); **Om P. Agrawal**, Los Altos, CA (US); **Fabiano Fontana**, San Jose, CA (US)

OTHER PUBLICATIONS

Lattice XP Family Data Sheet, Jun. 2006 and earlier, pp. 1-1 to 1-2, 2-1 to 2-28, and 6-1 to 6-2, Lattice Semiconductor Corporation.
MachXO Family Data Sheet, May 2006 and earlier, pp. 1-1 to 1-2, 2-1 to 2-22, and 7-1 to 7-2, Lattice Semiconductor Corporation.
Lattice Semiconductor Corporation, LatticeXP Family Data Sheet, Version 04.2, Mar. 2006, 127 pages.
Lattice Semiconductor Corporation, MachXO Family Data Sheet, Version 02.1, May 2006, 93 pages.

(73) Assignee: **Lattice Semiconductor Corporation**, Hillsboro, OR (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 319 days.

* cited by examiner

(21) Appl. No.: **11/446,308**

Primary Examiner—Vibol Tan
Assistant Examiner—Jason Crawford

(22) Filed: **Jun. 2, 2006**

(74) *Attorney, Agent, or Firm*—Haynes and Boone, LLP

(51) **Int. Cl.**
G01R 31/28 (2006.01)
G06F 21/00 (2006.01)

ABSTRACT

(52) **U.S. Cl.** 714/724; 714/727; 713/182
(58) **Field of Classification Search** 713/182–186;
714/724–727

Systems and methods are disclosed herein to provide techniques for providing programmable identification codes (ID-CODE) for PLDs. For example, in accordance with an embodiment of the present invention, a programmable logic device includes a first non-volatile memory adapted to store a first identification code of the programmable logic device, and a second memory adapted to store a second identification code of the programmable logic device. A control circuit selects between the first identification code stored in the first non-volatile memory and the second identification code stored in the second memory to provide as an identification code for the programmable logic device.


See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,325,368 A * 6/1994 James et al. 714/727
5,491,666 A * 2/1996 Sturges 365/201
5,734,868 A * 3/1998 Curd et al. 716/5
5,970,005 A * 10/1999 Yin et al. 365/201
6,922,820 B1 * 7/2005 Lulla et al. 716/4
7,216,275 B2 * 5/2007 Liang 714/727

19 Claims, 3 Drawing Sheets






Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5

1

PROGRAMMABLE LOGIC DEVICES WITH CUSTOM IDENTIFICATION SYSTEMS AND METHODS

TECHNICAL FIELD

The present invention relates generally to electrical circuits and, more particularly, to programmable logic devices, such as field programmable gate arrays with non-volatile memory.

BACKGROUND

A programmable logic device, such as field programmable gate array (FPGA) or a complex programmable logic device (CPLD), may be used in a variety of applications. A programmable logic device (PLD) offers the advantage of being reprogrammable in the field (e.g., while on the circuit board in its operational environment) to provide a wide range of programmable functions. A PLD may also provide certain advantages for implementing new product designs in integrated circuits relative to other traditional technologies (e.g., an application specific integrated circuit (ASIC) or an application specific standard product (ASSP)), such as for example, in terms of non-recurring engineering costs and other product development costs.

A conventional PLD typically supports the IEEE 1149.1 boundary scan test interface standard (also known as the JTAG standard) and therefore, for example, may be implemented as part of a JTAG scan chain. However, a drawback of a conventional PLD is that a user of the PLD cannot change the PLD's hard-wired 32-bit boundary scan identification code (IDCODE), which includes information regarding the manufacturer of the PLD along with device and version information. For example, a user of the PLD may want to change the identification code of the PLD so that the PLD will appear as the user's custom or proprietary device (e.g., the user's ASSP within the JTAG scan chain). As a result, there is a need for improved techniques directed towards PLD identification codes.

SUMMARY

In accordance with one embodiment of the present invention, a programmable logic device includes a first non-volatile memory adapted to store a first identification code of the programmable logic device; a second memory adapted to store a second identification code of the programmable logic device; and a control circuit adapted to select between the first identification code stored in the first non-volatile memory and the second identification code stored in the second memory to provide as an identification code for the programmable logic device.

In accordance with another embodiment of the present invention, a programmable logic device includes a first non-volatile means for storing a first identification code of the programmable logic device; a second means for storing a second identification code of the programmable logic device; and means for selecting between the first non-volatile-storing means and the second storing means to provide an identification code for the programmable logic device.

In accordance with another embodiment of the present invention, a method of providing an identification code for a programmable logic device includes storing within the programmable logic device a first identification code of the programmable logic device; providing a memory within the programmable logic device for storing a second identification code of the programmable logic device; and providing a cir-

2

cuit within the programmable logic device to programmably select between the first identification code and the second identification code to provide as an identification code for the programmable logic device.

The scope of the invention is defined by the claims, which are incorporated into this section by reference. A more complete understanding of embodiments of the present invention will be afforded to those skilled in the art, as well as a realization of additional advantages thereof, by a consideration of the following detailed description of one or more embodiments. Reference will be made to the appended sheets of drawings that will first be described briefly.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows a block diagram illustrating an exemplary programmable logic device in accordance with an embodiment of the present invention.

FIG. 2 shows a block diagram illustrating exemplary implementation details for a non-volatile memory and configuration memory of the programmable logic device of FIG. 1 in accordance with an embodiment of the present invention.

FIG. 3 shows a block diagram illustrating exemplary implementation details for providing a customized identification code for the programmable logic device of FIG. 1 in accordance with an embodiment of the present invention.

FIG. 4 shows a block diagram illustrating exemplary implementation details for a non-volatile memory of the programmable logic device of FIG. 1 in accordance with an embodiment of the present invention.

FIG. 5 shows a block diagram illustrating exemplary implementation details for providing a customized identification code for the programmable logic device of FIG. 1 in accordance with an embodiment of the present invention.

Embodiments of the present invention and their advantages are best understood by referring to the detailed description that follows. It should be appreciated that like reference numerals are used to identify like elements illustrated in one or more of the figures.

DETAILED DESCRIPTION

FIG. 1 shows a block diagram illustrating an exemplary programmable logic device (PLD) **100** in accordance with an embodiment of the present invention. PLD **100** (e.g., an FPGA) includes input/output (I/O) blocks **102** and programmable logic blocks **104**. I/O blocks **102** provide I/O functionality (e.g., supports one or more I/O and/or memory interface standards) for PLD **100**. Programmable logic blocks **104** (e.g., also referred to in the art as configurable logic blocks or logic array blocks) provide logic functionality for PLD **100**, such as for example LUT-based logic typically associated with FPGAs.

PLD **100** may also include reprogrammable non-volatile memory **106** (e.g., blocks of EEPROM or flash memory), volatile memory **108** (e.g., block SRAM), clock-related circuitry **110** (e.g., PLL circuits), one or more data ports **112**, configuration memory **114**, and/or an interconnect **116**. It should be understood that the number and placement of the various elements, such as I/O blocks **102**, logic blocks **104**, non-volatile memory **106**, volatile memory **108**, clock-related circuitry **110**, data port **112**, configuration memory **114**, and interconnect **116**, is not limiting and may depend upon the desired application. Furthermore, it should be understood that the elements are illustrated in block form for clarity and that certain elements, such as configuration memory **114** and interconnect **116**, would typically be distributed throughout

PLD **100**, such as for example in and between logic blocks **104**, to perform their conventional functions (e.g., storing configuration data that configures PLD **100** and providing routing resources, respectively).

Data port **112** may be used for programming PLD **100**, as would be understood by one skilled in the art. For example, data port **112(1)** may represent a programming port such as a central processing unit (CPU) port, also referred to as a peripheral data port or a sysCONFIG programming port. Data port **112(2)** may represent, for example, a programming port such as a joint test action group (JTAG) port by employing standards such as Institute of Electrical and Electronics Engineers (IEEE) 1149.1 and/or IEEE 1532 standards. Data ports **112(1)** and **112(2)** are not both required, but one or the other or both may be included to receive configuration data and commands.

Non-volatile memory **106** may be used to store configuration data within PLD **100** for transfer to configuration memory **114** of PLD **100** upon power up or during reconfiguration of PLD **100**. This may drastically reduce the time to reconfigure PLD **100** relative to an external bitstream (e.g., reduce the time from seconds to microseconds for loading of configuration data into configuration memory **114**).

Non-volatile memory **106** may also be used to provide background programming and/or storage for PLD **100** in accordance with some embodiments of the present invention. For example for storage functionality, non-volatile memory **106** may be used as non-volatile storage for a user or manufacture to store various test data, system management information, manufacturing control information, failure statistics information for board level diagnostics, security bits, identification codes, identification code selection bits (e.g., one or more custom ID fuses), and/or other information as desired and as explained further herein.

For example for background programming, PLD **100** may remain in user mode, based on the configuration data stored in configuration memory **114** within PLD **100**, while non-volatile memory **106** is programmed with new configuration data (e.g., a new user defined pattern). Once the new configuration data is stored in non-volatile memory **106**, this data can be transferred from non-volatile memory **106** to configuration memory **114** to reconfigure PLD **100**, a process sometimes referred to as refresh. The refresh process can be initiated by a signal or instruction provided to data port **112** (e.g., pulsing data port **112(1)** or providing a JTAG refresh instruction via data port **112(2)**).

As a specific example, FIG. 2 shows a block diagram illustrating a PLD **200**, which provides exemplary implementation details for PLD **100** of FIG. 1 in accordance with an embodiment of the present invention. PLD **200** includes non-volatile memory **106** (e.g., flash memory), configuration memory **114**, and control logic **202**.

Configuration memory **114** (e.g., volatile SRAM cells or other types of volatile or non-volatile memory) are used in a conventional manner to store configuration data, which determines the user defined functions of PLD **200** (e.g., determines programmable functions of I/O blocks **102**, logic blocks **104**, and interconnect **116**). Control logic **202** controls the internal transfer of the configuration data from non-volatile memory **106** to configuration memory **114**, as would be understood by one skilled in the art.

It should be understood that flash memory represents an exemplary type of memory for non-volatile memory **106**, but other types of non-volatile memory (e.g., EEPROM) that can be reprogrammed once or repeatedly may be substituted for non-volatile memory **106**. Furthermore for example in accordance with one or more embodiments of the present inven-

tion, either non-volatile memory **106** or configuration memory **114** may be programmed (i.e., receive and store information in its memory) to store configuration data for PLD **200**, but the device functionality of PLD **200** is determined by the information stored in configuration memory **114**. Thus, PLD **200** may be configured (including reconfiguration or partial reconfiguration), for example, when information is programmed into configuration memory **114**.

It should also be understood, in accordance with one or more embodiments of the present invention, that non-volatile memory **106** and configuration memory **114** may each be programmed (including reprogrammed), for example, via data port **112(1)** or data port **112(2)**, depending upon the desired application or design requirements. Further details regarding programming may be found in U.S. Pat. No. 6,828,823 and U.S. Patent Publication No. 2005-0189962-A1, published Sep. 1, 2005.

As noted herein, the JTAG standard specifies a 32-bit JTAG boundary scan identification code (IDCODE) to be unique for each type of device, such as PLD **100**. However, conventional approaches do not permit a user of a preprogrammed or a blank (e.g., un-programmed) PLD device to change the IDCODE so that the PLD device will behave and respond, for example, as the user's own "custom" device (e.g., as its own proprietary ASSP or PLD).

In contrast in accordance with one or more embodiments of the present invention, techniques are disclosed to provide a non-volatile PLD (e.g., FPGA) with a custom ID capability (e.g., custom IDCODE). For example in accordance with an embodiment of the present invention, a PLD is disclosed that allows a user the ability to customize the PLD to the user's application specific or custom needs by allowing the user to specify its own identification code (IDCODE) for the PLD rather than the fixed IDCODE provided by the manufacturer of the PLD. Consequently, if desired by a user of the PLD, the PLD may respond to the JTAG request (or scan) with the user's custom IDCODE rather than the hard-wired IDCODE set by the PLD manufacturer.

For example, FIG. 3 shows a circuit **300**, which illustrates exemplary implementation details for providing a customized identification code (IDCODE) for PLD **100** (or PLD **200**) of FIG. 1 in accordance with an embodiment of the present invention. Circuit **300** includes a non-volatile memory **302**, a memory **304**, and a multiplexer **306** as shown along with simplified exemplary JTAG details.

Non-volatile memory **302** may represent the hard-wired identification code (IDCODE) that may be provided in a conventional fashion (e.g., in ROM) or stored in some other form of non-volatile memory (e.g., non-volatile memory **106**). Memory **304** may represent non-volatile storage (e.g., within non-volatile memory **106** or other forms of non-volatile storage, such as ROM) or volatile memory, as explained further herein (e.g., in reference to FIG. 5), for a user-specified custom identification code (IDCODE) to be stored.

Circuit **300** also shows various exemplary conventional JTAG details (as would be understood by one skilled in the art), such as a JTAG state machine **312**, a JTAG instruction decoder **314**, JTAG registers **316**, and a JTAG select multiplexer **318**. Per the JTAG standard, circuit **300** includes a test data input (TDI) **320** and a test data output (TDO) **322** for circuit **300** to receive and provide various information.

Multiplexer **306** may be controlled to select the hard-wired identification code (IDCODE) stored in non-volatile memory **302** or the user-specified custom identification code (IDCODE) stored in memory **304** to provide on TDO **322** as the IDCODE for the PLD. As an example, a control signal to control multiplexer **306** may be provided, as shown in FIG. 3,

by a fuse 308 (also referred to herein as a custom ID fuse). Fuse 308, which may be a dedicated fuse, may represent for example one or more of the memory cells of non-volatile memory 106 or some other type of non-volatile memory technology. Consequently for example, depending upon the value stored by fuse 308, either the hard-wired identification code (IDCODE) stored in non-volatile memory 302 or the user-specified custom identification code (IDCODE) stored in memory 304 will be provided as an output signal 310 from multiplexer 306 to be provided on TDO 322 as the IDCODE.

For the IDCODE information, there are at least two ways to access the IDCODE register (e.g., non-volatile memory 302 or memory 304 depending upon which is selected by multiplexer 306), one by state and one by instruction (as would be understood by one skilled in the art). As set forth in the JTAG standard, moving directly from Test-Logic-Reset to Shift-DR will select the IDCODE register. Alternatively, loading the IDCODE instruction in Shift-IR will select the IDCODE register in Shift-DR. Therefore for the example above, a user by appropriately setting fuse 308 can control whether a custom ID Code from memory 304 or the manufacturer's ID code from non-volatile memory 302 is provided by the PLD as its identification code (IDCODE).

As a specific example, if fuse 308 (labeled ID_Select Fuse) is not programmed, then the contents of non-volatile memory 302 (e.g., the hard-wired identification code (IDCODE)) is provided to JTAG select multiplexer 318 to provide on TDO 322 as the IDCODE. Consequently if the IDCODE instruction is loaded into JTAG state machine 312, the hard-wired identification code (IDCODE) stored in non-volatile memory 302 is provided to TDO 322 to be read out. If fuse 308 is programmed, then the contents of memory 304 (e.g., the user-specified custom identification code (IDCODE)) is provided to JTAG select multiplexer 318 to provide on TDO 322 as the IDCODE. Consequently if the IDCODE instruction is loaded into JTAG state machine 312, the user-specified custom identification code (IDCODE) stored in memory 304 is provided to TDO 322 to be read out.

If JTAG state machine 312 is driven into a test-logic-reset (TLR) state, the IDCODE instruction is loaded automatically by JTAG state machine 312 and, therefore, there is no need to clock the IDCODE instruction into JTAG state machine 312 via TDI 320. The PLD containing circuit 300 can then be driven to Shift-DR state to shift out the IDCODE provided on TDO 322 (this technique also commonly known and referred to as scanning). Consequently, depending upon the value provided by fuse 308, either the hard-wired identification code (IDCODE) stored in non-volatile memory 302 or the user-specified custom identification code (IDCODE) stored in memory 304 will be provided on TDO 322 as the IDCODE.

The custom identification code (IDCODE) stored in memory 304 may be similar to the hard-wired identification code (IDCODE) stored in non-volatile memory 302 in terms of the number of bits (e.g., 32 bits) and the type of information stored. For example, the information provided as specified by the JTAG standard may include the manufacturer or user ID, part number of the PLD, and version.

A user programmable 32-bit boundary scan USERCODE register (e.g., to store a version number for version control of embedded applications) as described in the JTAG standard may also be provided and associated with non-volatile memory 302 and/or memory 304. Alternatively, memory 304 may represent the USERCODE register as set forth in the JTAG standard. Consequently, in accordance with one or more embodiments of the present invention, the USERCODE

register may be also used by a user to provide a programmable IDCODE, rather than the hard-wired IDCODE, via multiplexer 306.

For example as shown in FIG. 3, memory 304 (e.g., the USERCODE register) may store and provide the USERCODE (e.g., as programmed by a user) via JTAG select multiplexer 318 onto TDO 322 in a conventional fashion. Additionally as shown in FIG. 3, memory 304 (e.g., the USERCODE register) may store and provide the IDCODE (e.g., as programmed by a user) via multiplexer 306 and JTAG select multiplexer 318 onto TDO 322.

As noted above in accordance with an embodiment of the present invention, memory 304 and/or fuse 308 may represent a portion of non-volatile memory 106 (e.g., a flash memory block of PLD 100). For example, non-volatile memory 106 may be partitioned into different sections, with one section for non-volatile storage of configuration data that can be transferred to configuration memory 114 and another section for non-volatile storage of other information, such as the user's custom ID code and custom ID fuse value.

As a specific implementation example, FIG. 4 shows a block diagram illustrating exemplary implementation details for a non-volatile memory 400 of PLD 100 of FIG. 1 in accordance with an embodiment of the present invention. Specifically as an example, non-volatile memory 400 may represent a specific implementation example for non-volatile memory 106, with non-volatile memory 400 partitioned (segmented) into a trim portion 402 (labeled TRIM), a test portion 404 (labeled PES), and a configuration data portion 406 (labeled config flash).

Trim portion 402 is optional and may be used to store trim data, which may be used for adjusting or trimming various parameters within PLD 100 (e.g., adjusting current source values, resistor values, or other circuit parameters as would be understood by one skilled in the art). Test portion 404 (e.g., also referred to as program electronic signature (PES) in one embodiment) may be used to store test or design data and other types of information, as desired by a user. Configuration data portion 406 may be used to store configuration data for transfer to configuration memory 114 to reconfigure PLD 100. Non-volatile memory 400 (e.g., flash memory) may have a different starting address 408, as shown, for each portion or section.

Fuse 308 and/or memory 304, which contains the custom identification code (IDCODE) or a user code (USERCODE), may be formed as part of non-volatile memory 400 (e.g., flash memory). For example, fuse 308 and/or memory 304 may be located within test portion 404 of non-volatile memory 400. Consequently, memory 304 (e.g., non-volatile flash memory) and fuse 308 would not require a separate erasure process and, for example, may be on the same flash row as the test data, security bits, and/or encryption fuses and share the same erasure process.

As an example, memory 304 and fuse 308 may be disposed within the PLD so as to avoid the accidental erasure of these values when programming the PLD with new configuration data. In general, a user typically may not want the IDCODE and fuse value to be erased during a bulk erase or erase all instructions provided to the PLD. For example, memory 304 and fuse 308 may only be erased by a manufacturing enabled erase.

If some form of security is implemented for the PLD, such as security bits that may be set in a conventional fashion to prevent unauthorized access to the PLD or to prevent the programming or reading out of the programmed data from the PLD, then depending upon the implementation of memory 304 and fuse 308, a user may have to program the IDCODE

and the value of fuse **308** prior to setting the security features of the PLD, which may prevent any further changes to the values stored as the IDCODE or the fuse value.

If a user programs fuse **308** to provide the user's custom ID code, the PLD manufacturer's programming software may not recognize the device in the JTAG scan chain without being provided with the custom ID code to recognize as a particular device. However, the PLD manufacturer's programming software would still be able to program the PLD if the hard-wired ID code provided by the manufacturer was accessible by using the standard JTAG procedures.

For example, a user may desire to program the PLD to operate as an ASSP that may only be programmed or reprogrammed to support the user's specific IP. Thus, the user could program the value of fuse **308** (custom ID fuse) so that the custom IDCODE of the user is provided as the PLD's ID code during scanning (JTAG scan to acquire the IDCODE). Consequently, only the user's specific programming tool will recognize the PLD based upon the user's custom IDCODE and the customer can control the distribution of its ASSP solution. Furthermore, the PLD manufacturer could program the PLD with a user's desired IDCODE value prior to shipment to the user and may further mark (e.g., by text, colors, indentations, or other conventional means for identifying) the PLD so that the PLD could be distinguished visually as an ASSP version of the PLD as compared to the standard version of the PLD.

Circuit **300** (FIG. 3) illustrates in accordance with one or more embodiments of the present invention an exemplary implementation for providing a user the ability to provide either the hard-wired IDCODE or a user-specified IDCODE. As another example, FIG. 5 shows a circuit **500**, which illustrates exemplary implementation details for providing a customized identification code (IDCODE) for PLD **100** of FIG. 1 in accordance with an embodiment of the present invention. Circuit **500** is similar to circuit **300**, but provides another implementation example for selectively providing the user-specified IDCODE.

Specifically, circuit **500** further includes a non-volatile memory **502** and a multiplexer **506**. For this example, memory **304** may represent volatile SRAM memory (e.g., a number of SRAM cells of configuration memory **114**), which may store a USERCODE or an IDCODE as programmed by a user of the PLD that includes circuit **500**. Non-volatile memory **502** may represent any form of non-volatile memory, such as for example a portion of non-volatile memory **106** (e.g., test portion **404**), which may also store a USERCODE or an IDCODE as programmed by a user of the PLD.

Consequently as shown in FIG. 5, non-volatile memory **302** or memory **304** may be selected to provide its stored data as the IDCODE onto TDO **322** for the PLD via multiplexer **306** and JTAG select multiplexer **318**. Furthermore, non-volatile memory **502** or memory **304** may be selected to provide its stored data onto TDO **322** as the USERCODE for the PLD via multiplexer **504** and JTAG select multiplexer **318**. Multiplexer **504** may be controlled by a control signal **506** (labeled Flash mode), which for example may be provided by a fuse as described similarly for multiplexer **306** and fuse **308**.

As an example of operation, a user may program memory **304** to store a custom IDCODE (a User IDCODE), program fuse **308** with a logical low value (i.e., a "0") to control multiplexer **306** to select memory **304**, program non-volatile memory **502** to store a USERCODE, and provide a logical high value (i.e., a "1") with control signal **506** to control multiplexer **504** to select non-volatile memory **502**. Consequently, memory **304** will provide its programmed IDCODE

as the IDCODE for the PLD when requested per the JTAG standard, while non-volatile memory **502** will provide its programmed USERCODE as the USERCODE for the PLD when requested per the JTAG standard.

Additionally in accordance with one or more embodiments of the present invention, the information stored in non-volatile memory **502** may be transferred (downloaded) to memory **304**, as desired by a user (e.g., via control logic **202**). Consequently for example, a new USERCODE or custom IDCODE may be programmed into non-volatile memory **502** (e.g., during a background programming operation) while the PLD continues to operate and memory **304** continues to provide its currently stored information (e.g., IDCODE or USERCODE, depending upon selection by multiplexers **306** and **504**). The user may then transfer the new information from non-volatile memory **502** to memory **304**, when desired, so that memory **304** may provide the new information (e.g., IDCODE or USERCODE). It should also be understood that a number of custom IDCODES and/or USERCODES may be stored by additional memories and selected and provided as the PLD's IDCODE and USERCODE by utilizing the techniques discussed herein in accordance with one or more embodiments of the present invention.

Systems and methods are disclosed herein to provide techniques for providing programmable ID codes for PLDs. For example, in accordance with an embodiment of the present invention, a PLD is disclosed that allows a user to use the hard-wired IDCODE value provided with the PLD or allow a user to program into the PLD a custom IDCODE value. Consequently for example, a user may program the PLD to function as its custom device, such as an ASSP.

Embodiments described above illustrate but do not limit the invention. It should also be understood that numerous modifications and variations are possible in accordance with the principles of the present invention. Accordingly, the scope of the invention is defined only by the following claims.

What is claimed is:

1. A programmable logic device comprising:

- a JTAG state machine;
- a JTAG instruction decoder coupled to the JTAG state machine;
- a JTAG multiplexer coupled to the JTAG instruction decoder and a control circuit;
- a first non-volatile memory adapted to store a first identification code of the programmable logic device;
- a second memory adapted to store a second identification code of the programmable logic device; and
- the control circuit adapted to select between the first identification code stored in the first non-volatile memory and the second identification code stored in the second memory to provide as an identification code for the programmable logic device,

wherein the control circuit comprises:

- a multiplexer coupled to the first non-volatile memory and the second memory; and
- a third non-volatile memory adapted to control the multiplexer to provide one of the first identification code and the second identification code as a multiplexer output signal to the JTAG multiplexer to provide as the identification code on a test data output path.

2. The programmable logic device of claim 1, wherein the first non-volatile memory has stored therein a hard-wired identification code as the first identification code, and the second identification code is a user-provided customized identification code.

3. The programmable logic device of claim 1, further comprising:

9

a third memory adapted to store at least one of a third identification code and a user code of the programmable logic device;

wherein the second memory is further adapted to store at least one of the second identification code and a user code of the programmable logic device; and

wherein the control circuit is further adapted to select between the second memory and the third memory to provide a user code for the programmable logic device.

4. The programmable logic device of claim 1, wherein the second memory and the third non-volatile memory are formed as part of a flash memory block.

5. The programmable logic device of claim 1, wherein the second memory and the third non-volatile memory are formed as part of a flash memory block, and wherein the flash memory block is partitioned into a configuration data portion and a test data portion, with the second memory and the third non-volatile memory forming a part of the test data portion.

6. The programmable logic device of claim 1, wherein the second memory is coupled to the JTAG multiplexer and adapted to provide a USERCODE of the programmable logic device.

7. The programmable logic device of claim 1, wherein the second memory comprises a USERCODE register for the programmable logic device.

8. The programmable logic device of claim 1, further comprising:

a first port adapted to support a JTAG standard;

a plurality of input/output blocks;

a plurality of logic blocks;

an interconnect adapted to programmably connect the input/output blocks and the logic blocks; and

a configuration memory adapted to receive configuration data via the first port to configure the input/output blocks, the logic blocks, and the interconnect.

9. The programmable logic device of claim 1, wherein the programmable logic device is externally marked to distinguish from a programmable logic device that does not include the second memory.

10. A programmable logic device comprising:

a first non-volatile means for storing a first identification code of the programmable logic device;

a second means for storing a second identification code of the programmable logic device;

means for selecting between the first non-volatile storing means and the second storing means to provide an identification code for the programmable logic device;

a third means for storing at least one of a third identification code and a user code of the programmable logic device, wherein the second storing means is further adapted to store a user code of the programmable logic device in the event that the second storing means is not storing the second identification code, and wherein the selecting means is further adapted to select between the third storing means and the second storing means to provide a user code of the programmable logic device; and means for transferring data from the third storing means to the second storing means.

11. The programmable logic device of claim 10, further comprising means for supporting a JTAG standard, wherein the selecting means provides the identification code to the supporting means to provide on a test data output terminal,

10

and wherein the second storing means is further adapted to store a user code of the programmable logic device to provide to the supporting means in the event that the second storing means is not storing the second identification code.

12. The programmable logic device of claim 10, further comprising means for distinguishing externally the programmable logic device from a programmable logic device not storing the second identification code.

13. The programmable logic device of claim 10, further comprising:

means for receiving JTAG information and providing

JTAG information, wherein the information provided includes the identification code;

a plurality of input/output blocks;

a plurality of logic blocks;

an interconnect adapted to programmably connect the input/output blocks and the logic blocks; and

a configuration memory adapted to receive configuration data via the JTAG receiving means to configure the input/output blocks, the logic blocks, and the interconnect.

14. A programmable logic device (PLD) comprising:

a JTAG state machine;

a JTAG instruction decoder coupled to the JTAG state machine;

a JTAG multiplexer coupled to the JTAG instruction decoder and a control circuit;

a first memory adapted to store a first PLD identification code;

a second memory adapted to store a second PLD identification code; and

the control circuit adapted to select between the first PLD identification code stored in the first memory and the second PLD identification code stored in the second memory and further adapted to provide the selected PLD identification code to the JTAG multiplexer.

15. The programmable logic device of claim 14, wherein the first memory is ROM and the second memory is reprogrammable non-volatile memory.

16. The programmable logic device of claim 14, wherein the second memory is coupled to the JTAG multiplexer and adapted to provide a user code of the programmable logic device.

17. The programmable logic device of claim 14, further comprising:

a third memory adapted to store at least one of a third PLD identification code and a user code of the programmable logic device;

wherein the second memory is further adapted to store at least one of the second PLD identification code and a user code of the programmable logic device; and

wherein the control circuit is further adapted to select between the second memory and the third memory to provide a user code for the programmable logic device.

18. The programmable logic device of claim 17, wherein the third memory is adapted to transfer to the second memory one of a PLD identification code and a user code of the programmable logic device.

19. The programmable logic device of claim 17, wherein the second memory is volatile memory and the third memory is reprogrammable non-volatile memory.

* * * * *